



PRODUCT SPECIFICATIONS DOMO VarioSlide S Pro 40

Applications	Soccer	
Fibre	Polyethylene / UV-stabilized / Straight / Combination fibre / 16.000 dtex Monofilament 12.000 dtex/ ca. 300 µm thickness / S profile Heliflex XP Tape, ca. 120 µm thickness	
Production Method	Linear tufting	
Gauge	5/8"	
# stitches / lm	130 / lm	± 10%
# tufts / m ²	8.190 / m ²	± 10%
# piles / m ²	114.660 / m ²	± 10%
Pile Height	40 mm	± 5%
Pile Weight	1.220 gr / m ²	± 10%
Total Height	42 mm	± 5%
Total Weight	2.490 gr / m ²	± 10%
Tuft Cloth	Polypropylene, UV-stabilized, ca. 270 gr / m ²	± 5%
Backing	Latex, ca. 1.000 gr / m ²	± 10%
Infill	System & material related (see laboratory test reports)	
Shock pad	System & material related (see laboratory test reports)	
Roll Width	400 cm	
Roll Length	As per lay-out	
Colour	Green	
Colour Lines	White / Yellow	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 3.000 hours UV-A	
Water Permeability	6.10 ⁻⁴ m/sec	
Pile Anchorage	> 30 N	

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE