

NURTEKS

WE ARE GOOD AT THIS GAME

60 mm

ATLAS GRASS XQS FIFA



High Resilience



Natural Experience



Best Tuft Bind



Eco Friendly



Texturing Process



Certifiable



Equal Ball Roll



Bi Colour



Reduced Glare



www.nurteks.com.tr



Applications : Professional Football, Rugby & GAA
Manufacturer : Nurteks Halı San. AŞ
Production : Tufted Cut Pile

Fiber

Fiber Component : 100 % PE Monofilament, UV Resistant
Fiber Weight : 12000/6 D-Tex
Fiber Thickness : 310 microns

Primary Backing

Composition/Structure : H18 Layer Polyethylene
Weight : 235 gr/m²

Secondary Backing

Backing Type : Carboxylated SBR Lateks, 4 mm perforation holes
Coating Weight : 1100 gr/m²
Water Permeability : 40 Lt min/m²

Pile Features

Pile Height : 60 mm
Total Height : 62 mm
Total Pile Weight : 1350 gr/m² (±5%)
Stitches : 9000 tufts per m² (±5%)
Total Weight : 2950 gr/m² (±5%)
Number of Tufts : 13/10 cm
Gauge : 5/8 inch (1,59 cm)

Infill

Stabilizing Infill : Fine Graded Silica Sand. Appr. 15 kg/m²
Performance Infill : Black SBR Rubber. Appr. 17 kg/m²

Installation

Roll Length : According to production Schedule
Bonding : PU based adhesive with joining tape
Shockpad / E-Layer : N/A

