

NURTEKS

WE ARE GOOD AT THIS GAME

60 mm

DUOFLAMENT S



High Resilience



Natural Experience



Best Tuft Bind



Eco Friendly



Texturing Process



Certifiable



Equal Ball Roll



Bi Colour



Reduced Glare



www.nurteks.com.tr



Applications : Professional Football, Rugby & GAA
Manufacturer : Nurteks Halı San. AŞ
Production : Tufted Cut Pile

Fiber

Fiber Component : 100 % PE Monofilament, UV Resistant
Fiber Weight : 12000/6 D-Tex
Fiber Thickness : 310 microns

Primary Backing

Composition/Structure : H16 Layer Polyethylene
Weight : 165 gr/m²

Secondary Backing

Backing Type : Carboxylated SBR Lateks, 4 mm perforation holes
Coating Weight : 1100 gr/m²
Water Permeability : 40 Lt min/m²

Pile Features

Pile Height : 60 mm
Total Height : 62 mm
Total Pile Weight : 1375 gr/m² (±5%)
Stitches : 8223 tufts per m² (±5%)
Total Weight : 2640 gr/m² (±5%)
Number of Tufts : 13/10 cm
Gauge : 5/8 inch (1,59 cm)

Infill

Stabilizing Infill : Fine Graded Silica Sand. Appr. 20 kg/m²
Performance Infill : Black SBR Rubber. Appr. 16 kg/m²

Installation

Roll Length : According to production Schedule
Bonding : PU based adhesive with joining tape
Shockpad / E-Layer : N/A

