



PRODUCT SPECIFICATIONS DOMO VarioSlide S Pro 60

Applications	Soccer
Fibre	Polyethylene / UV-stabilized / Straight / Combination fibre / 16.000 dtex Monofilament 12.000 dtex/ ca. 300 µm thickness / S profile Heliflex XP Tape, ca. 120 µm thickness
Production Method	Linear tufting
Gauge	5/8"
# stitches / lm	130 / lm ± 10%
# tufts / m ²	8.190 / m ² ± 10%
# piles / m ²	114.660 / m ² ± 10%
Pile Height	60 mm ± 5%
Pile Weight	1.700 gr / m ² ± 10%
Total Height	62 mm ± 5%
Total Weight	2.970 gr / m ² ± 10%
Tuft Cloth	Polypropylene, UV-stabilized, ca. 270 gr / m ² ± 5%
Backing	Latex, ca. 1.000 gr / m ² ± 10%
Infill	See laboratory test reports
Shock pad	See laboratory test reports
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Lines	White / Yellow
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 3.000 hours UV-A
Water Permeability	6.10 ⁻⁴ m/sec
Pile Anchorage	> 30 N

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE

DOMO® SPORTS GRASS IS A BRAND OF SPORTS & LEISURE GROUP NV

Industriepark-West 43 | B - 9100 Sint-Niklaas F | +32 (0)3 780 45 73 | T +32 (0)3 780 45 75 | domosportgrass.com