

NURTEKS

WE ARE GOOD AT THIS GAME

REVOLUTION DBF



High Resilience



Natural Experience



Best Tuft Bind



Eco Friendly



Texturing Process



Certifiable



Equal Ball Roll



Bi Colour



Reduced Glare



www.nurteks.com.tr



Applications : Professional Football, FIFA Q
Manufacturer : Nurteks Halı San. AŞ
Production : Tufted Cut Pile

Fiber

Fiber Component : 7100 DTEX PE
: 6720/8 DTEX PE
: 13200/6 DTEX PE

Fiber Weight : 19920/6 D-Tex
Fiber Thickness : 360 micron 13200/6 DTEX
160 micron 6720 DTEX

Primary Backing

Composition/Structure : H16 Layer Polyethylene
Weight : 165 gr/m²

Secondary Backing

Backing Type : Carboxylated SBR Lateks, 4 mm perforation holes
Coating Weight : 1250 gr/m²
Water Permeability : 40 Lt min/m²

Pile Features

Pile Height : 30 mm
Total Height : 32 mm
Total Pile Weight : 3.600 gr/m² (±%5)
Stitches : 64.200+10.250+10.250 tufts per m² (±%5)
Total Weight : 5.000 gr/m² (±%5)
Number of Tufts : 32+17,5/10 cm
Gauge : 3/16 - 5/16 inches

Infill

Performance Infill : Organic Infill Appr. 2,5 kg/m²

Installation

Roll Length : According to production Schedule
Bonding : PU based adhesive with joining tape
Shockpad / E-Layer : Foamex 13mm

